FUJITSU

Data Sheet
Fujitsu PRIMERGY TX200 S6 Server

Well-balanced price- performance

PRIMERGY TX tower servers are ideal for use in SMEs or branch offices. They increase operational efficiency by providing rock solid, record-breaking, energy efficient performance. That performance is built on 20-years of pioneering work in Green IT. As a customer, you benefit from a reduction in your organization's environmental impact and lower running costs. The reliability is proven by testing the machines through 5000 boot cycles – far more than other vendors do. PRIMERGY TX servers are also easy to manage via the PRIMERGY ServerView Suite, reducing IT admin workload and costs. Plus, tower to rack conversion kits are available for most TX systems, ensuring investment protection.

PRIMERGY TX200 S6
The PRIMERGY TX200 S6 is a perfect server for small or decentralized infrastructures in an attractive family design. The PRIMERGY TX200 S6 offers expandability, energy efficiency and dual processor performance. With up to 16 2.5" hard disks, you can save on an external storage unit. The high energy efficiency minimizes costs. Moreover, a maximum of 96GB of RAM, redundancy features, and the performance of up to two Intel® Xeon® processors 5600 series allow you to make a great start into virtualization. The PRIMERGY TX200 S6 also lends itself as a departmental, email or web server. A tower to rack conversion kit protects your investment's lifetime. This great system strikes the right balance between price and performance.

http://www.fujitsu.com/

Features and Benefits

Main Features	Benefits
■ Intel® Xeon® Processor 5600 Series with up to 6 core operation (up to 12 threads per socket with Hyper Threading), 12 MB shared cache, Internal Memory Management Unit (3 channels of DDR3 memory) and Intel® Turbo Boost Optimization	■ Higher overall productivity with leading-edge technology and the performance of up to two processors!
■ Up to 96GB RAM configurable in independent, mirrored, spare or performance modes	■ Plenty of memory configurable to suit your every need: file, print, database or virtualization server
■ Hot-plug power supply with 92% efficiency (85% efficiency for standard power supply)	■ Save energy costs and minimize the environmental impact
■ Up to 4 (6 optional) 3,5 hard disks or 8 (16 optional) 2,5 SAS or SATA hard disk drives and 6 expansion slots (4 PCIe Gen 2, 1 PCIe, 1 PCI)	■ Choose among a range of expansion variables to suit your budget and requirements.
■ Hot-plug hard disks included as standard, plus optional: hot-plug redundant power supply units or redundant fans or ServerView Local Service Panel (LSP).	■ Tailor made availability, offering the security level you need.

Technical details

PRIMERGY TX200 S6						
Housing types	Tower	Tower	Tower	Tower	Rack	Rack
Storage drive architecture	6x 3.5" SAS/SATA	6x 3.5" SAS/SATA	16x 2.5" SAS/SATA/ SSD	16x 2.5" SAS/SATA/ SSD	6x 3.5" SAS/SATA	16x 2.5" SAS/SATA/ SSD
Power supply	Standard	Hot-plug	Standard	Hot-plug	Hot-plug	Hot-plug

Mainboard	
Mainboard type	D 2799
Chipset	Intel® 5500
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5500 series / Intel® Xeon® processor E5600 series / Intel® Xeon® processor L5600 series / Intel® Xeon® processor X5600 series
Processor	Intel® Xeon® processor E5503 (2C/2T, 2.00 GHz, SLC: 4 x 256 KB, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W) Intel® Xeon® processor E5603 (4C/4T, 1.60 GHz, SLC: -, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W) Intel® Xeon® processor E5606 (4C/4T, 2.13 GHz, SLC: -, TLC: 8 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W) Intel® Xeon® processor E5607 (4C/4T, 2.26 GHz, SLC: -, TLC: 8 MB, Turbo: No, 4.8 GT/s, Mem bus: 1066 MHz, 80 W) Intel® Xeon® processor E5620 (4C/8T, 2.40 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W) Intel® Xeon® processor E5640 (4C/8T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W) Intel® Xeon® processor E5645 (6C/12T, 2.40 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 5.86 GT/s, Mem bus: 1333 MHz, 80 W) Intel® Xeon® processor E5649 (6C/12T, 2.53 GHz, SLC: -, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 5.86 GT/s, Mem bus: 1333 MHz, 80 W) Intel® Xeon® processor L5609 (4C/4T, 1.86 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 40 W) Intel® Xeon® processor L5630 (4C/8T, 2.13 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 40 W) Intel® Xeon® processor L5640 (6C/12T, 2.26 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3/4/4, 6.4 GT/s, Mem bus: 1333 MHz, 60 W) Intel® Xeon® processor X5650 (6C/12T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W) Intel® Xeon® processor X5660 (6C/12T, 2.80 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)
Memory slots	12 (6 DIMMs per CPU, 3 channels with 2 slots per channel)
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	2 GB - 96 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Hot-spare memory support Memory Mirroring support
Memory notes	max. 96 GB registered, min. 2 GB unbuffered; memory mirroring with 2 identical modules, hot-spare memory with three identical modules per channel

Memory Modules Independent Mode	2 GB (1 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
	2 GB (1 module(s) 2 GB) DDR3 LV, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
Memory Modules Mirrored Mode	4 GB (2 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (2 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (2 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (2 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (2 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
Memory Modules Spare or Performance Mode	6 GB (3 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	12 GB (3 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	12 GB (3 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	24 GB (3 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	24 GB (3 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Interfaces

USB ports	10 x USB 2.0 (3x front USB, 4x rear USB 3x internal for backup, USSD and internal USB)
Graphics (15-pin)	1 x VGA
Serial 1 (9-pin)	1 x serial RS-232-C (9 pin), usable for iRMC S2 or System or common use
Serial 2 (9-pin)	1 x serial RS-232-C (9 pin), optional - occupies an unused slot
LAN / Ethernet (RJ-45)	1 x Gbit/s Ethernet (Intel Hartwell)
Service LAN (RJ45)	Service LAN traffic can be switched to shared onboard Gbit LAN port
	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s)

Onboard or integrated Controller

SATA Controller	ICH10R, 6-port SATA (4x for internal hard disks, 2x for accessible drives)
SATA controller type notes	On board SATA controller supports RAID levels 0, 1, 10
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)

Slots

PCI-Express 2.0 x4 (mech. x8)	2 x Full height (1x long, 1x short)
PCI-Express 2.0 x8	2 x Full height (1 slot is notched. It is therefore also usable for x16 cards operating in x8 mode).
PCI-Express x4 (mech. x8)	1 x Full height
PCI-slots	1 x
Slot Notes	PCI slot: 32-bit / 33 MHz, 5 V; in SAS-configurations 1x PCI-Express slot is occupied by the modular RAID controller.
Storage drive bay configuration	4x 3.5-inch, for SAS / SATA or 8x 2.5-inch for SAS/SATA optional
Accessible drive bays	3 x 5.25/1.6-inch
Notes accessible drives	All possible options described in relevant system configurator.
Optional hard disk bays	2 x 3.5-inch hot-plug SAS/SATA or 8x 2.5-inch hot-plug SAS in HDD box (occupies 2x 5.25-inch bays)

Fan Configuration

Fan configuration	2 standard fans or 2 redundant fans (only available in combination with hot plug redundant power supply)

Operating panel

Operating buttons	On/off switch
	NMI button
	Reset button

Operating panel	
Status LEDs	System status (orange / yellow)
	Identification (blue)
	Hard disks access (green)
	Power (amber / green)
	At system rear side:
	System status (orange / yellow)
	Identification (blue)
	LAN connection (green)
	LAN speed (green / yellow)
Service display	Optional:
	ServerView Local Service Panel (LSP)

BIOS	
BIOS features	ROM based setup utility
	Recovery BIOS
	BIOS settings save and restore
	Local BIOS update from USB device
	Online update tools for main Windows and Linux versions
	Local and remote update via ServerView Update Manager
	SMBIOS V2.4
	Remote PXE boot support

Operating Systems and Virtualization Software	
Certified or supported operating systems and virtualization software	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows® Web Server 2008 R2
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Windows® Small Business Server 2008 Standard
	Microsoft® Windows® Small Business Server 2008 Premium
	Microsoft® Windows Server® 2003 Enterprise Edition
	Microsoft® Windows Server® 2003 Standard Edition
	Microsoft® Windows Server® 2003 Web Edition
	VMware vSphere™ 5.0 Embedded
	VMware vSphere™ 5.0
	VMware vSphere™ 4.1
	VMware vSphere™ 4.1 Embedded
	VMware vSphere™ 4.1 Installable
	VMware vSphere™ 4.0
	VMware vSphere™ 4.0 Embedded
	VMware vSphere™ 4.0 Installable
	Novell® SUSE Linux Enterprise Server 11
	Novell® SUSE Linux Enterprise Server 10
	Novell® SUSE Linux Enterprise Server 10 with XEN
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
	Red Hat® Enterprise Linux 5 with XEN
	Citrix® XenServer®
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	ServerView Suite - Deploy
	SV Installation Manager
	SV Scripting Toolkit
	SV Deployment Manager (30-day trial version)
	ServerView Suite - Control
	SV Operations Manager incl. PDA and ASR & R
	(Prefailure and Analysis; Automatic Server Recovery and Restart)
	SV Performance Management
	SV Power Management
	SV RAID Manager
	ServerView Suite - Maintain
	SV Remote Management (iRMC)
	SV Update Management (BIOS, Firmware, Windows Drives and SV Agents)
	SV Asset Management
	SV Online Diagnostics
	ServerView Suite - Integrate
	SV Integration packs e.g. for Microsoft System Center, Nagios, HP, SIM, HP NNM, IBM Tivoli, Altiris
	Deployment Solutions and others
Option	ServerView Suite - Deploy
	SV Deployment Manager (full version)
	ServerView Suite - Maintain
	iRMC Advanced Pack incl. Advanced Video Redirection (AVR) and Remote Storage
	ServerView Suite - Dynamize
	SV Virtual-IO Manager (VIOM)
	SV Resource Orchestrator Virtual Edition (ROR VE)
	SV Resource Orchestrator Cloud Edition (ROR CE)
	ServerView Suite - Integrate
	SV Integration pack for Fujitsu ManageNow® solution
Server Management notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.

Dimensions / Weight

Floor-stand (W x D x H)	205 (306) x 584 x 444 mm
Rack (W x D x H)	482 x 570 x 220 mm
Dimension notes	Floorstand Width 306 mm with tilt protection; depth measured excludes handles on redundant PSU. Rack depth excludes handles of redundant PSU and rack front.
Mounting Depth Rack	596 mm
Height Unit Rack	5 U
Weight	up to 36,8 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

Environmental

Operating ambient temperature	10 - 35℃
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	34 dB(A) (idle) / 36 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	5.2 B (idle) / 5.7 B (operating)
Noise notes / description	measured with standard fans and PSU

Electrical values

Power supply configuration	1x standard, 1x hot-plug or 2x redundant
Max. output of single power supply	685 W
Standard power supply output	700 W (85% efficiency)
Hot-plug power supply output	800 W (92% efficiency)

Electrical values

Hot-plug power supply redundancy	Yes
Rated voltage range	100 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	9.5 - 4.0A
Rated current in basic configuration	1,3 0.6A
Active power (min. configuration)	111 W
Active power (max. configuration)	461 W
Apparent power (max. configuration)	490 VA
Heat emission	1659.6 kJ/h (1573.0 BTU/h)
Power Supply Notes	In case of using an UPS we recommend to select a 1500VA/1000 W type as a minimum, because high power peaks might be possible when switching over to battery!

The following Energy Star Familiy configuration options use less energy and reduce greenhouse gas emissions:

 TX200 S6 E-StarFam1

http://ts.fujitsu.com/products/standard_servers/e_efficient.html

Compliance

Germany	TÜV GS
Europe	CE Class A *
USA/Canada	CSAc/us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Japan	VCCI Class A + JIS 61000-3-2
Australia/New Zealand	C-Tick
Taiwan	BSMI
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Components

Storage disks	SSD SATA, 3 Gb/s, 64 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SATA, 3 Gb/s, 32 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 400 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 200 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 100 GB, SLC, hot-plug, 2.5-inch, enterprise
	HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, economic
	HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 3 Gb/s, 320 GB, 5400 rpm, hot-plug, 2.5-inch, economic
	HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 3.5-inch, economic
	HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 3 Gb/s, 160 GB, 7200 rpm, hot-plug, 3.5-inch, economic
	HDD SATA, 3 Gb/s, 160 GB, 5400 rpm, hot-plug, 2.5-inch, economic
	HDD SATA, 3 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SAS, 6 Gb/s, 900 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 600 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 600 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 450 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 450 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 73 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
Backup Drives	DDS Gen5, 36 GB, 3 MB/s, half height, USB 2.0
	DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
	LTO2HH Ultrium, 200 GB, 24 MB/s, half height, SAS 3Gb/s
	LTO3HH Ultrium, 400 GB, 60 MB/s, half height, SAS 3Gb/s
	LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s
	LTO5HH Ultrium, 1500 GB, 140 MB/s, half height, SAS 6Gb/s
	RDX Drive, 160 GB, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 2.0
Optical drives	Blu-ray Disc™ Triple Writer, (4x BD-RW; 16x DVD; 40x CD), half height, SATA I
	Blu-ray Disc™ Triple Writer, (6x BD-ROM ; 8x DVD; 24x CD), slimline, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
	DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I
SCSI / SAS Controller	SCSI Ctrl. 320 MB 1ch int/ext PCIe x1
	SAS Ctrl. 6 Gb 8 ports ext. PCIe Gen2 x8
	SAS Ctrl. 3 Gb 4 ports int. / 4 ports ext. PCIe x4

RAID Controller	Integrated RAID 5/6 Ctrl., HDD SAS 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
	Integrated RAID 0/1 Ctrl., SAS/SATA 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, No BBU support (based on LSI SAS2008)
	Integrated RAID 0/1 Ctrl., SAS/SATA 3 Gb, 8 ports int. RAID level: 0, 1, 1E, No BBU support (based on LSI 1068e)
	Integrated RAID 0/1 Ctrl., SAS/SATA 3 Gb, 4 ports int. RAID level: 0, 1, 1E, No BBU support (based on LSI 1064e)
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 8 Gb Qlogic QLE2560 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gb Qlogic QLE2562 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 8 Gb Emulex LPe1250 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gb Emulex LPe12002 MMF LC-style
LAN Controller	Ethernet Ctrl. 1 x 1 Gb Intel® Gigabit CT Desktop Adapter
	Ethernet Ctrl. 1 x 1 Gb Intel® PRO/1000 PF Server Adapter
	Ethernet Ctrl. 1 x 1 Gb Intel® PRO/1000 PT Server Adapter
	Ethernet Ctrl. 2 x 10 Gb Fujitsu Eth Ctrl 2x10Gbit PCIe x8 D2755 SFP+
	Ethernet Ctrl. 2 x 1 Gb Fujitsu LAN Adapter D2735-2
	Ethernet Ctrl. 4 x 1 Gb Fujitsu Eth Ctrl 4x1Gbit PCIe x4 D2745 Cu
Rack infrastructure	Cable Arm 2U for PCR M1 S and 3rd party racks
	Rackmount kit full extraction (760mm), tool less mounting
	Cable Management for asym. 19-inch PRIMECENTER Racks

Warranty	
Standard Warranty	3 years
Service level	On-site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	5 years
Service Weblink	http://www.fujitsu.com/fts/services

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY TX200 S6, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX200 S6, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
 http://www.fujitsu.com/PRIMERGY

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

Disclaimer